



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
08/987,775	12/09/1997	ACHIM GREFENSTEIN	47587/48070	6702
26474	7590	06/01/2006	EXAMINER	
NOVAK DRUCE DELUCA & QUIGG, LLP			KRUEER, KEVIN R	
1300 EYE STREET NW			ART UNIT	
SUITE 400 EAST TOWER			PAPER NUMBER	
WASHINGTON, DC 20005			1773	

DATE MAILED: 06/01/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary

Application No.

08/987,775

Applicant(s)

GREFENSTEIN ET AL.

Examiner

Kevin R. Krueer

Art Unit

1773

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 15 March 2006.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 24,26,30,31,34,41 and 43 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 24,26,30,31,34,41 and 43 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All b) ☐ Some * c) ☐ None of:
1. ☒ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152) |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Continued Examination Under 37 CFR 1.114

1. A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 7/26/2004 has been entered.

Claim Rejections - 35 USC § 103

The text of those sections of Title 35, U.S. Code not included in this action can be found in a prior Office action.

2. Claims 24, 31, and 41 are rejected under 35 U.S.C. 103(a) as being unpatentable over Fischer et al. (US 5,747,568) in view of WO96/09928 (aka Sallmetall) and JP 61-026646 (herein referred to as Yutaka).

Fischer teaches a molding material comprising 30-80wt% of an elastomeric grafting base and 20-70wt% of a shell grafted onto the grafting base (abstract). The grafting base comprises 90-99.9% of at least one alkyl acrylate and 0.1-10wt% of a polyfunctional crosslinking monomer. The shell comprises 0-100% styrene or substituted styrenes, and 0-100% of an acrylonitrile or methyl methacrylate. The above-described particles are dispersed in a hard matrix comprising 60-90wt% styrene or substituted styrene and 10-40% acrylonitrile (col 1, lines 48-col2, line 16). The composition may further contain up to 30t% of additives such as fibers (Col 4, lines 26-

Art Unit: 1773

34). This composition exhibit good weather resistance, aging resistance, and high impact strength (col 4, lines 46-53), and are usable as signs (col 4, line 48).

Fischer does not teach that the molding material may be overlaid with a PMMA transparent layer and a transparent protective film. However, Sallmetall teaches a light transmitting cover foil intended for adhesion to an information-carrying surface (page 1, lines 1-5). The first layer of the cover foil comprises a deformable plastic (abstract). The examiner interprets the taught deformable plastic layer to read on the claimed transparent protective film of claim 41 because it will inherently provide the film with some layer of protection. The deformable plastic layer may be textured or patterned if desired (page 1, lines 30+). The cover foil further comprises a dimensionally stable carrier layer comprising, for instance, PMMA (abstract). The examiner notes that the taught dimensionally stable carrier layer reads on Applicant's claimed "transparent top layer of PMMA." A thermally activated hot melt layer comprising EVA, EEA, EBA, EMA, GBA or other low melting thermoplastics may be utilized to adhere the deformable plastic to the carrier sheet (abstract). The layers may be mutually connected via coextrusion (page 2, lines 14-16). It would have been obvious to one of ordinary skill in the art to utilize the cover film taught in Sallmetall on the sign taught in Fischer in order to protect the sign and provide the sign with the desired texturing and patterning.

Fischer also does not teach that the composition may comprise a polycarbonate. However, Yutaka teaches that the appearance and high impact resistance of a core/shell graft copolymer may be improved by compounding it with 5-95wt% polycarbonate (abstract). Thus, it would have been obvious to one of ordinary skill in

Art Unit: 1773

the art at the time the invention was made to compound the core/shell graft copolymer taught in Fischer with 5-95wt% polycarbonate. The motivation for doing so would have been to improve the composition's appearance and high impact resistance.

3. Claims 24, 31, 32, 34, and 41 are rejected under 35 U.S.C. 103(a) as being unpatentable over Fischer et al. (US 5,747,568) in view of Ellison US 5,985,079) and JP 61-026646 (herein referred to as Yutaka).

Fischer teaches a molding material comprising 30-80wt% of an elastomeric grafting base and 20-70wt% of a shell grafted onto the grafting base (abstract). The grafting base comprises 90-99.9% of at least one alkyl acrylate and 0.1-10wt% of a polyfunctional crosslinking monomer. The shell comprises 0-100% styrene or substituted styrenes, and 0-100% of an acrylonitrile or methyl methacrylate. The above-described particles are dispersed in a hard matrix comprising 60-90wt% styrene or substituted styrene and 10-40% acrylonitrile (col 1, lines 48-col2, line 16). The composition may further contain up to 30t% of additives such as fibers (Col 4, lines 26-34). This composition exhibit good weather resistance, aging resistance, and high impact strength (col 4, lines 46-53), and are usable as automobile parts (col 4, line 48).

Fischer does not teach the application of transparent surface coatings to the taught composition. However, Ellison teaches a flexible composite surfacing film for providing a substrate with desired surface characteristics. The film comprises a flexible transparent outer polymer clear coat layer and a pigmented base coat layer is adhered to said outer clear coat layer and is visible there through (abstract). The transparent outer polymer clear coat layer may comprise outer and inner layers of differing

Art Unit: 1773

properties. For example, both layers may comprise a blend of fluorinated polymer and an acrylic resin. However, the outer layer may be rich in the fluorinated polymer to enhance weatherability, and the inner layer may be rich in acrylic resin to improve bonding to the pigmented layer (col 7, lines 15-37). The acrylic resin may be polymethyl methacrylate homopolymers (col 6, lines 24-42). Both polymers may be extruded from the same extrusion die (col 7, line 40). The pigmented polymer may also be extruded (col 8, line 35). The surfacing film may be applied to polymeric supporting substrates in accordance with known laminating or bonding techniques. Particularly suitable shaped articles of the invention are exterior automobile parts (col 11, line 36). Thus, it would have been obvious to one of ordinary skill in the art to apply the surfacing film taught in Ellison to the composition taught in Fischer in order to supply the composition with the desired surface characteristics.

Fischer also does not teach that the composition may comprise a polycarbonate. However, Yutaka teaches that the appearance and high impact resistance of a core/shell graft copolymer may be improved by compounding it with 5-95wt% polycarbonate (abstract). Thus, it would have been obvious to one of ordinary skill in the art at the time the invention was made to compound the core/shell graft copolymer taught in Fischer with 5-95wt% polycarbonate. The motivation for doing so would have been to improve the composition's appearance and high impact resistance.

4. Claims 24, 31, and 41 are rejected under 35 U.S.C. 103(a) as being unpatentable over Rosenau et al. (US 5,821,302) in view of Ellison (US 5,985,079). Rosenau teaches a thermoplastic molding composition comprising (a) 50-100wt% of a

Art Unit: 1773

styrene compound, and (b) 0.1-70wt% of a graft polymer. The styrene compound may comprise 0-40wt% acrylonitrile. The graft polymer comprises 30-90wt% of a core, and 10-70wt% of a graft shell. The core comprises 50-99.99wt% of C1-10 alkyl acrylate, and 0.01-5wt% of a polyfunctional crosslinking monomer. The shell comprises 50-100wt% styrene and 0-40wt% acrylonitrile (col 1, lines 4-65). The graft polymer has an average particle diameter of less than 700nm. The composition may further comprise up to 70wt% of a particulate polymer and up to 70wt% of a polycarbonate blend (col 9, lines 59+). The composition is useful in extrusions, injection moldings, calendaring, and rolling (col 10, lines 58-64). The composition is especially useful in exterior applications, such as automobile construction (col 10, lines 65+).

Rosenau does not teach the claimed top coat or protective coat may be applied to the taught composition. However, Ellison teaches a flexible composite surfacing film for providing a substrate with desired surface characteristics. The film comprises a flexible transparent outer polymer clear coat layer and a pigmented base coat layer is adhered to said outer clear coat layer and is visible there through (abstract). The transparent outer polymer clear coat layer may comprise outer and inner layers of differing properties. For example, both layers may comprise a blend of fluorinated polymer and an acrylic resin. However, the outer layer may be rich in the fluorinated polymer to enhance weatherability, and the inner layer may be rich in acrylic resin to improve bonding to the pigmented layer (col 7, lines 15-37). The acrylic resin may be polymethyl methacrylate homopolymers (col 6, lines 24-42). Both polymers may be extruded from the same extrusion die (col 7, line 40). The pigmented polymer may also

Art Unit: 1773

be extruded (col 8, line 35). The surfacing film may be applied to polymeric supporting substrates in accordance with known laminating or bonding techniques. Particularly suitable shaped articles of the invention are exterior automobile parts (col 11, line 36). Thus, it would have been obvious to one of ordinary skill in the art to apply the surfacing film taught in Ellison to the composition taught in Rosenau in order to supply the composition with the desired surface characteristics.

5. Claims 24, 31, and 39 are rejected under 35 U.S.C. 103(a) as being unpatentable over Rosenau et al. (US 5,821,302) in view of Trabert et al. (US 5,318,737). Rosenau teaches a thermoplastic molding composition comprising (a) 50-100wt% of a styrene compound, and (b) 0.1-70wt% of a graft polymer. The styrene compound may comprise 0-40wt% acrylonitrile. The graft polymer comprises 30-90wt% of a core, and 10-70wt% of a graft shell. The core comprises 50-99.99wt% of C1-10 alkyl acrylate, and 0.01-5wt% of a polyfunctional crosslinking monomer. The shell comprises 50-100wt% styrene and 0-40wt% acrylonitrile (col 1, lines 4-65). The graft polymer has an average particle diameter of less than 700nm. The composition may further comprise up to 70wt% of a particulate polymer and up to 70wt% of a polycarbonate component (col 9, lines 59+). The composition is useful in extrusions, injection moldings, calendaring, and rolling (col 10, lines 58-64), and may be utilized to make automotive parts.

Rosenau does not teach that a transparent PMMA coating should be applied over the taught composition. However, Trabert teaches a capstock composition comprising an acrylic polymer and an acrylic based impact-modifying agent (abstract).

Art Unit: 1773

The acrylic resin may comprise polymerized methyl methacrylate (col 6, line 16). The composition has particularly good flexural modulus and impact strength (col 5, line 27), scratch resistance, thermal resistance, and chemical resistance. Such resin compositions can be extruded onto the desired substrate (col 5, lines 29+) or coextruded with the substrate (col 5, lines 48+). The capstocks are especially useful with structural plastics (col 9, lines 1+). It would have been obvious to one of ordinary skill in the art to coextrude the capstock taught in Trabert with the composition taught in Rosenau in order to improve its chemical resistance, and impact strength.

6. Claims 24, 31, and 41 are rejected under 35 U.S.C. 103(a) as being unpatentable over Rosenau et al. (US 5,821,302) in view of EP006421 (aka Endoh). Rosenau teaches a thermoplastic molding composition comprising (a) 50-100wt% of a styrene compound, and (b) 0.1-70wt% of a graft polymer. The styrene compound may comprise 0-40wt% acrylonitrile. The graft polymer comprises 30-90wt% of a core, and 10-70wt% of a graft shell. The core comprises 50-99.99wt% of C1-10 alkyl acrylate, and 0.01-5wt% of a polyfunctional crosslinking monomer. The shell comprises 50-100wt% styrene and 0-40wt% acrylonitrile (col 1, lines 4-65). The graft polymer has an average particle diameter of less than 700nm. The composition may further comprise up to 70wt% of a particulate polymer and up to 70wt% of a polycarbonate blend (col 9, lines 59+). The composition is useful in extrusions, injection moldings, calendaring, and rolling (col 10, lines 58-64).

Rosenau does not teach that a PMMA transparent layer or a protective topcoat may be applied to the taught composition. However, Endoh teaches an extrusion

Art Unit: 1773

laminate comprising a polyvinylidene fluoride layer, and an adhesive layer comprising a methyl methacrylate polymer (abstract). The methyl methacrylate polymer may comprise PMMA (page 9, lines 14+). The polyvinylidene fluoride layer provides the laminate with excellent weather resistance and chemical resistance. Thus, it would have been obvious to one of ordinary skill in the art to extrude the composition taught in Rosenau with the polyvinylidene fluoride and PMMA layers taught in Endoh in order to improve the composition's weather and chemical resistance.

7. Claims 24, 31, and 41 are rejected under 35 U.S.C. 103(a) as being unpatentable over Fischer et al. (US 5,747,568) in view of EP0060421 (aka Endoh) and JP 61-026646.

Fischer teaches a molding material comprising 30-80wt% of an elastomeric grafting base and 20-70wt% of a shell grafted onto the grafting base (abstract). The grafting base comprises 90-99.9% of at least one alkyl acrylate and 0.1-10wt% of a polyfunctional crosslinking monomer. The shell comprises 0-100% styrene or substituted styrenes, and 0-100% of an acrylonitrile or methyl methacrylate. The above-described particles are dispersed in a hard matrix comprising 60-90wt% styrene or substituted styrene and 10-40% acrylonitrile (col 1, lines 48-col2, line 16). The composition may further contain up to 30t% of additives such as fibers (Col 4, lines 26-34). This composition exhibit good weather resistance, aging resistance, and high impact strength (col 4, lines 46-53), and are usable as signs (col 4, line 48).

Fischer does not teach that a PMMA transparent layer or a protective topcoat may be applied to the taught composition. However, Endoh teaches an extrusion

Art Unit: 1773

laminate comprising a polyvinylidene fluoride layer, and an adhesive layer comprising a methyl methacrylate polymer (abstract). The methyl methacrylate polymer may comprise PMMA (page 9, lines 14+). The polyvinylidene fluoride layer provides the laminate with excellent weather resistance and chemical resistance. Thus, it would have been obvious to one of ordinary skill in the art to extrude the composition taught in Fischer with the polyvinylidene fluoride and PMMA layers taught in Endoh in order to improve the composition's weather and chemical resistance.

Fischer also does not teach that the composition may comprise a polycarbonate. However, Yutaka teaches that the appearance and high impact resistance of a core/shell graft copolymer may be improved by compounding it with 5-95wt% polycarbonate (abstract). Thus, it would have been obvious to one of ordinary skill in the art at the time the invention was made to compound the core/shell graft copolymer taught in Fischer with 5-95wt% polycarbonate. The motivation for doing so would have been to improve the composition's appearance and high impact resistance.

8. Claim 30 is rejected under 35 U.S.C. 103(a) as being unpatentable over (a) Fischer et al. (US 5,747,568) in view of WO96/09928 (aka Sallmetall) and Yutaka, (b) Fischer et al. (US 5,747,568) in view of Ellison US 5,985,079) and Yutaka, (c) Rosenau et al. (US 5,821,302) in view of Ellison (US 5,985,079), (d) Rosenau et al. (US 5,821,302) in view of Trabert et al. (US 5,318,737), (e) Rosenau et al. (US 5,821,302) in view of EP0060421 (aka Endoh), or (f) Fischer et al. (US 5,747,568) in view of EP0060421 (aka Endoh) and Yutaka, as applied above, and further in view of Tsai et al. (US 5,858,550). Fischer in view of Sallmetall, Fischer in view of Ellison, Rosenau in

Art Unit: 1773

view of Trabert, Rosenau in view of Endoh, Fischer in view of Endoh, and Rosenau in view of Ellison are relied upon as above. However, none of the references teach that the ratio of MFI values of the individual components of the laminated sheet is not more than 3:1. However, Tsai teaches that the constituents used to form a coextruded sheet should have melt properties that are substantially similar to one another (col 7, lines 51+). Thus, it would have been obvious to one of ordinary skill in the art to utilize resins that have MFI values substantially similar to one another so that the films can be effectively coextruded.

9. Claims 26 is rejected under 35 U.S.C. 103(a) as being unpatentable over (a) Fischer et al. (US 5,747,568) in view of WO96/09928 (aka Sallmetall) and Yutaka, (b) Fischer et al. (US 5,747,568) in view of Ellison US 5,985,079) and Yutaka, (c) Rosenau et al. (US 5,821,302) in view of Ellison (US 5,985,079), (d) Rosenau et al. (US 5,821,302) in view of Trabert et al. (US 5,318,737), (e) Rosenau et al. (US 5,821,302) in view of EP0060421 (aka Endoh), or (f) Fischer et al. (US 5,747,568) in view of EP0060421 (aka Endoh) and Yutaka, as applied above. Fischer in view of Sallmetall, Fischer in view of Ellison, Rosenau in view of Trabert, Rosenau in view of Endoh, Fischer in view of Endoh, and Rosenau in view of Ellison are relied upon as above. None of the references teaches the desired thickness of the laminate. However, Rosenau and Fischer each teach rigid compositions with enhanced impact resistance. Furthermore, Ellison, Trabert, Sallmetall, and Endoh each teach the application of protective layers to such substrates. Thus, it would have been obvious to one of ordinary skill in the art to vary the thickness of the laminate so that the laminate has the

Art Unit: 1773

desired rigidity, impact resistance, and weather resistance for the intended end use.

Furthermore, it would have been obvious to one of ordinary skill in the art to vary the thickness of the substrate composition in order to obtain the desired rigidity and impact resistance in the final product.

10. Claim 43 is rejected under 35 U.S.C. 103(a) as being unpatentable over Fischer et al. (US 5,747,568) in view of Zabrocki et al (US 5,306,548) or McDonagh (US 4,169,180) and Yutaka.

Fischer teaches a molding material comprising 30-80wt% of an elastomeric grafting base and 20-70wt% of a shell grafted onto the grafting base (abstract). The grafting base comprises 90-99.9% of at least one alkyl acrylate and 0.1-10wt% of a polyfunctional crosslinking monomer. The shell comprises 0-100% styrene or substituted styrenes, and 0-100% of an acrylonitrile or methyl methacrylate. The above-described particles are dispersed in a hard matrix comprising 60-90wt% styrene or substituted styrene and 10-40% acrylonitrile (col 1, lines 48-col2, line 16). The composition may further contain up to 30t% of additives such as fibers (Col 4, lines 26-34). This composition exhibit good weather resistance, aging resistance, and high impact strength (col 4, lines 46-53), and are usable as signs (col 4, line 48).

Fischer does not teach that a styrene-acrylonitrile copolymer layer may be applied to the taught composition. However, Zabrocki teaches a weatherable film for lamination to an underlying substrate. The film comprises an outer layer of weather resistant polymer comprising styrene/acrylonitrile copolymer or butyl acrylate-reinforced styrene/acrylonitrile copolymer (abstract). The film can be utilized with high impact

Art Unit: 1773

polystyrene substrates (see example 1). NOTE: the composition taught in Fischer is a HIPS composition. For a definition of a HIPS, Applicant's attention is directed to US 4,749,737 (see col 5, lines 27+). Thus, it would have been obvious to one of ordinary skill in the art to apply the styrene-acrylonitrile weatherable film taught in Zabrocki to the composition taught in Fischer in order to improve said composition's weather resistance.

Similarly, McDonagh teaches a protective layer comprising methacrylate/crosslinked styrene-acrylonitrile/uncrosslinked styrene-acrylonitrile (abstract). Said composition is applied to base layers that lack superior weather resistance (abstract). Thus, it would have been obvious to one of ordinary skill in the art to apply the protective layer taught in McDonagh to the composition taught in Fischer in order to improve its weather resistance.

Fischer also does not teach that the composition may comprise a polycarbonate. However, Yutaka teaches that the appearance and high impact resistance of a core/shell graft copolymer may be improved by compounding it with 5-95wt% polycarbonate (abstract). Thus, it would have been obvious to one of ordinary skill in the art at the time the invention was made to compound the core/shell graft copolymer taught in Fischer with 5-95wt% polycarbonate. The motivation for doing so would have been to improve the composition's appearance and high impact resistance.

11. Claim 43 is rejected under 35 U.S.C. 103(a) as being unpatentable over Rosenau et al. (US 5,821,302) in view of Zabrocki et al (US 5,306,548) or McDonagh (US 4,169,180). Rosenau teaches a thermoplastic molding composition comprising (a)

Art Unit: 1773

50-100wt% of a styrene compound, and (b) 0.1-70wt% of a graft polymer. The styrene compound may comprise 0-40wt% acrylonitrile. The graft polymer comprises 30-90wt% of a core, and 10-70wt% of a graft shell. The core comprises 50-99.99wt% of C1-10 alkyl acrylate, and 0.01-5wt% of a polyfunctional crosslinking monomer. The shell comprises 50-100wt% styrene and 0-40wt% acrylonitrile (col 1, lines 4-65). The graft polymer has an average particle diameter of less than 700nm. The composition may further comprise up to 70wt% of a particulate polymer and up to 70wt% of a polycarbonate blend (col 9, lines 59+). The composition is useful in extrusions, injection moldings, calendaring, and rolling (col 10, lines 58-64), and may be utilized to make automotive parts.

Rosenau does not teach that a styrene-acrylonitrile copolymer layer may be applied to the taught composition. However, Zabrocki teaches a weatherable film for lamination to an underlying substrate. The film comprises an outer layer of weather resistant polymer comprising styrene/acrylonitrile copolymer or butyl acrylate-reinforced styrene/acrylonitrile copolymer (abstract). The film can be utilized with high impact polystyrene substrates (see example 1). NOTE: the composition taught in Rosenau is a HIPS composition. For a definition of a HIPS, Applicant's attention is directed to US 4,749,737 (see col 5, lines 27+). Thus, it would have been obvious to one of ordinary skill in the art to apply the styrene-acrylonitrile weatherable film taught in Zabrocki to the composition taught in Rosenau in order to improve said composition's weather resistance.

Art Unit: 1773

Similarly, McDonagh teaches a protective layer comprising methacrylate/crosslinked styrene-acrylonitrile/uncrosslinked styrene-acrylonitrile (abstract). Said composition is applied to base layers that lack superior weather resistance (abstract). Thus, it would have been obvious to one of ordinary skill in the art to apply the protective layer taught in McDonagh to the composition taught in Rosenau in order to improve its weather resistance.

Response to Arguments

Applicant's arguments filed March 15, 2006 have been fully considered but they are not persuasive.

Applicant arguments with regard to polycarbonate are addressed above in the modified rejections. Said modifications were necessitated by amendment.

Applicant argues the declaration filed 9 September 2003 and the results in table 2 of the specification demonstrate unexpected results with respect to gloss and scratch resistance and penetration energy. The examiner maintains the position that said examples do not give a representative sampling of the claimed composition across the claimed ranges of components A-D. Thus, the showing is not commensurate in scope with the claims. While the examiner acknowledges the showing does not have to be over the entire range, but the evidence supported by evidence based on must enable one of ordinary skill in the art to determine a trend in the exemplified data which would allow the artisan to reasonably extend the probative value thereof to the entirety of the claimed range. Said showing has not been made/argued.

Art Unit: 1773

Applicant further argues the examine has merely picked and chosen different layers from various sources of cited art. The examiner respectfully disagrees and notes that each modification contains the requisite motivation for making said modification. Since applicant has not specifically argued how the examiner erred in the patentability determination, the rejections are maintained. The examiner notes the Office has not conceded that the suggestion to combine did not come from the prior art, but is unable to fully respond to said argument since it is unclear where applicant alleges the examiner made said concession. With regard to the statement on page 13 of the non-final office action, the examiner was merely noting that the Office never relied upon the references for the motivation that Applicant said was lacking.

Conclusion

Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire **THREE MONTHS** from the mailing date of this action. In the event a first reply is filed within **TWO MONTHS** of the mailing date of this final action and the advisory action is not mailed until after the end of the **THREE-MONTH** shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of

Art Unit: 1773

the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Kevin R. Kruer whose telephone number is 571-272-1510. The examiner can normally be reached on Monday-Friday.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Carol Chaney can be reached on 571-272-1284. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

A handwritten signature in black ink, appearing to read 'K. R. Kruer', is positioned above the printed name.

Kevin R. Kruer
Patent Examiner-Art Unit 1773